



Thermal Transfer Self-Wound Overlamine Product Recommendation Guide



Made in
the USA



8035 Lake Winds Drive
PO Box 418
Oak Harbor, OH 43449

800-793-TAPE (8273)
419-898-TAPE (8273)
www.acpo.com

Self-Wound Polypropylene Overlaminates



**505T Polypropylene
1.3 Mil**

CLEAR

Thermal Transfer Ribbon Recommendations


**F = Flat Head Printers Used in Testing:
Zebra 140Xi Series and Zebra 170Xi Series**


**N = Near Edge Printers Used in Testing:
TEC B472, TEC BSX4, TEC B-SX4T, TEC B572**





**531T Polypropylene
1.5 Mil**


MATTE

859-689-2100	 Thermal Transfer by ARBOR	PRINTER	MATERIAL		DESCRIPTION		
			505T BOPP Clear	531T BOPP Matte	Wax	Wax/Resin	Resin
	AXR EL	F	Excellent	Excellent			X
	AXR 8	F	Very Good				X
	AXR 1	F	Excellent	Excellent			X
	AXR 7+	F	Excellent	Good			X

888-569-7222		PRINTER	MATERIAL		DESCRIPTION		
			505T BOPP Clear	531T BOPP Matte	Wax	Wax/Resin	Resin
	R300	F	Good				X
	R510HF	F	Very Good				X
	R550	F	Good				X
	R600	F	Excellent				X

800-326-1249	 CORPORATION	PRINTER	MATERIAL		DESCRIPTION		
			505T BOPP Clear	531T BOPP Matte	Wax	Wax/Resin	Resin
	LA6	F	Excellent	Good		X	
	LA5	F	Good	Good		X	
	HF29	N	Very Good	Very Good			X
	HL72	F	Very Good	Very Good			X

888-464-4625		PRINTER	MATERIAL		DESCRIPTION		
			505T BOPP Clear	531T BOPP Matte	Wax	Wax/Resin	Resin
	Primemark	F	Good	Good		X	
	SP330	F	Excellent	Very Good			X

877-887-3456		PRINTER	MATERIAL		DESCRIPTION		
			505T BOPP Clear	531T BOPP Matte	Wax	Wax/Resin	Resin
	B128	F	Excellent	Excellent		X	
	B325	F	Good	Good			X
	B324	F	Good				X
	B112	N	Good				X

These recommendations are based on compatibility testing performed by the listed ribbon vendors using acpo overlaminates. At acpo Ltd., we require the end user perform thorough testing in their printing environment, using their own equipment to determine suitability for specific label applications

Self-Wound Polyester Overlaminates



610T Polyester 1.42 Mil
692T Polyester 1.42 Mil - UL

CLEAR

Thermal Transfer Ribbon Recommendations

F = Flat Head Printers Used in Testing:
Zebra 140Xi Series and Zebra 170Xi Series

N = Near Edge Printers Used in Testing:
TEC B472, TEC BSX4, TEC B-SX4T, TEC B572



631T Polyester
1.42 Mil

MATTE

859-689-2100	inkanto Thermal Transfer by ARMOR	PRINTER	MATERIAL		DESCRIPTION		
			610T/692T PET Clear	631T PET Matte	Wax	Wax/Resin	Resin
	AXR EL	F	Excellent				X
	AXR 8	F	Excellent				X
	AXR 1	F	Excellent	Good			X
	AXR 7+	F	Excellent	Good			X

888-569-7222	DNP	PRINTER	MATERIAL		DESCRIPTION		
			610T/692T PET Clear	631T PET Matte	Wax	Wax/Resin	Resin
	TRX-55	F		Good		X	
	MP Mid	F		Good		X	
	B300	F	Very Good				X
	R600	F	Excellent				X

800-326-1249	DYNIC USA CORPORATION	PRINTER	MATERIAL		DESCRIPTION		
			610T/692T PET Clear	631T PET Matte	Wax	Wax/Resin	Resin
	LA6	F		Excellent		X	
	LA5	F		Excellent		X	
	LA 3+	F		Very Good		X	
	LA 7	F		Very Good		X	

888-464-4625	iimak	PRINTER	MATERIAL		DESCRIPTION		
			610T/692T PET Clear	631T PET Matte	Wax	Wax/Resin	Resin
	Primemark	F	Good	Good		X	
	SP330	F	Excellent	Very Good			X

877-887-3456	TW / Specialty Films	PRINTER	MATERIAL		DESCRIPTION		
			610T/692T PET Clear	631T PET Matte	Wax	Wax/Resin	Resin
	B128	F	Good	Excellent		X	
	B324	F	Very Good	Good			X
	B325	F	Very Good	Good			X
	B814	F	Very Good	Excellent			X

These recommendations are based on compatibility testing performed by the listed ribbon vendors using acpo overlaminates. At acpo Ltd., we require the end user perform thorough testing in their printing environment, using their own equipment to determine suitability for specific label applications



acpo ltd. maintains the highest quality manufacturing standards while providing customers with innovative self-wound overlamination products, exceptional service, superior quality and on-time service.

An ISO 9001 certified company we use Lean Manufacturing principles with focus on continuous improvement to insure we are meeting all our current and future product and service expectations.

We are a one stop shop for all your pressure sensitive roll label films. Contact our world class customer service and sales teams and we will offer you a solution to all your overlamine needs.

Sales, Order Entry, Customer Service

Phone: 800-793-TAPE (8273)

Fax: 877-675-5344

www.acpo.com



Self-Wound Overlamine Film

POLYPROPYLENE

Glitter

Clear

Matte

FDA Compliant Direct

Food Contact

Photoluminescent

Thermal Transfer



POLYESTER

Clear

Matte

Easy Release

FDA Compliant

Removable

Thermal Transfer

UL Recognized

UV Screening

Flexible Packaging Films

Overlaminates for Digital Printers

Overlaminates on Liner

Paint Mask

Unsupported Films

Toll Coating

Custom Slitting

Form/Tag Reinforcements

Carton Sealing Tape

These recommendations are based on compatibility testing performed by the listed ribbon vendors using acpo overlaminates. At acpo ltd., we require the end user perform thorough testing in their printing environment, using their own equipment to determine suitability for specific label applications